

DORIAN WHITE RECT 60X120

REFERENCE SIZE (cm) THICKNESS (mm) GROUP

A033149 60x120 10,20 PC BIA GL



DIMENSIONS AND SURFACE PROPERTIES

Size, thickness, side straightness, flatness, orthogonality UNE-EN 14411 It accomplished all requeriments

DH	YSICAL PROPERTIES	
711	TOTORE PROPERTIES	
Water absorption capacity	EN ISO 10545-03	< 0,5%
Flexion resistance	EN ISO 10545-04	=> 45 N/mm ²
Abrasion resistance (glazed Ceramic)	EN ISO10545-07	IV
Thermal shock resistance	EN ISO 10545-09	It stands the test
Cracking resistance	EN ISO 10545-11	It stands the test
Frost resistance	EN ISO 10545-12	It stands the test

CHEMICAL PROPERTIES		
Resistance to acids	EN ISO 10545-13	GHA
Resistance to alcalis	EN ISO 10545-13	GHA
Resistance to cleaning products	EN ISO 10545-13	GLA
Resistance to chemical products in swimming pool water	EN ISO 10545-13	GLA
Stains resistance	EN ISO 10545-14	3

ANTI-SLIP CHARACTERISTICS









DORIAN WHITE RECT 60X60

REFERENCE SIZE (cm) THICKNESS (mm) GROUP

A018634 60X60 8,90 PC BIA GL



DIMENSIONS AND SURFACE PROPERTIES

Size, thickness, side straightness, flatness, orthogonality UNE-EN 14411 It accomplished all requeriments

	PHYSICAL PROPERTIES	
Water absorption capacity	EN ISO 10545-03	< 0,5%
Flexion resistance	EN ISO 10545-04	$=> 51 \text{ N/mm}^2$
Abrasion resistance (glazed Ceramic)	EN ISO10545-07	IV
Thermal shock resistance	EN ISO 10545-09	It stands the test
Cracking resistance	EN ISO 10545-11	It stands the test
Frost resistance	EN ISO 10545-12	It stands the test

CHEMICAL PROPERTIES		
Resistance to acids	EN ISO 10545-13	GHA
Resistance to alcalis	EN ISO 10545-13	GHA
Resistance to cleaning products	EN ISO 10545-13	GLA
Resistance to chemical products in swimming pool water	EN ISO 10545-13	GLA
Stains resistance	EN ISO 10545-14	3

ANTI-SLIP CHARACTERISTICS









DORIAN WHITE RECT 30X60

REFERENCE SIZE (cm) THICKNESS (mm) GROUP

A018638 30X60 9,30 PC BIA GL



DIMENSIONS AND SURFACE PROPERTIES

Size, thickness, side straightness, flatness, orthogonality

UNE-EN 14411

It accomplished all requeriments

	PHYSICAL PROPERTIES	
Water absorption capacity	EN ISO 10545-03	< 0,5%
Flexion resistance	EN ISO 10545-04	$=>40 \text{ N/mm}^2$
Abrasion resistance (glazed Ceramic)	EN ISO10545-07	IV
Thermal shock resistance	EN ISO 10545-09	It stands the test
Cracking resistance	EN ISO 10545-11	It stands the test
Frost resistance	EN ISO 10545-12	It stands the test

CHEMICAL PROPERTIES		
Resistance to acids	EN ISO 10545-13	GHA
Resistance to alcalis	EN ISO 10545-13	GHA
Resistance to cleaning products	EN ISO 10545-13	GLA
Resistance to chemical products in swimming pool water	EN ISO 10545-13	GLA
Stains resistance	EN ISO 10545-14	3

ANTI-SLIP CHARACTERISTICS









ROD. DORIAN WHITE 7,5X60

REFERENCE SIZE (cm) THICKNESS (mm) GROUP

A019268 7,5x60 PC BIA GL 9,20



DIMENSIONS AND SURFACE PROPERTIES

PHYSICAL PROPERTIES

EN ISO 10545-12 Frost resistance It stands the test









DORIAN GRAPHITE RECT 60X120

REFERENCE SIZE (cm) THICKNESS (mm) GROUP

A033148 60x120 10,20 PC BIA GL



DIMENSIONS AND SURFACE PROPERTIES

Size, thickness, side straightness, flatness, orthogonality UNE-EN 14411 It accomplished all requeriments

	PHYSICAL PROPERTIES	
Water absorption capacity	EN ISO 10545-03	< 0,5%
Flexion resistance	EN ISO 10545-04	$=>45 \text{ N/mm}^2$
Abrasion resistance (glazed Ceramic)	EN ISO10545-07	III
Thermal shock resistance	EN ISO 10545-09	It stands the test
Cracking resistance	EN ISO 10545-11	It stands the test
Frost resistance	EN ISO 10545-12	It stands the test

CHEMICAL PROPERTIES		
Resistance to acids	EN ISO 10545-13	GHA
Resistance to alcalis	EN ISO 10545-13	GHA
Resistance to cleaning products	EN ISO 10545-13	GLA
Resistance to chemical products in swimming pool water	EN ISO 10545-13	GLA
Stains resistance	EN ISO 10545-14	3

ANTI-SLIP CHARACTERISTICS









DORIAN GRAPHITE RECT 60X60

REFERENCE SIZE (cm) THICKNESS (mm) GROUP

A018636 60X60 9,80 PC BIA GL



DIMENSIONS AND SURFACE PROPERTIES

Size, thickness, side straightness, flatness, orthogonality UNE-EN 14411 It accomplished all requeriments

	PHYSICAL PROPERTIES	
Water absorption capacity	EN ISO 10545-03	< 0,5%
Flexion resistance	EN ISO 10545-04	$=>45 \text{ N/mm}^2$
Abrasion resistance (glazed Ceramic)	EN ISO10545-07	III
Thermal shock resistance	EN ISO 10545-09	It stands the test
Cracking resistance	EN ISO 10545-11	It stands the test
Frost resistance	EN ISO 10545-12	It stands the test

CHEMICAL PROPERTIES		
Resistance to acids	EN ISO 10545-13	GHA
Resistance to alcalis	EN ISO 10545-13	GHA
Resistance to cleaning products	EN ISO 10545-13	GLA
Resistance to chemical products in swimming pool water	EN ISO 10545-13	GLA
Stains resistance	EN ISO 10545-14	3

ANTI-SLIP CHARACTERISTICS









DORIAN GRAPHITE RECT 30X60

REFERENCE SIZE (cm) THICKNESS (mm) GROUP

A018640 30X60 8,80 PC BIA GL



DIMENSIONS AND SURFACE PROPERTIES

Size, thickness, side straightness, flatness, orthogonality UNE-EN 14411 It accomplished all requeriments

PH	IYSICAL PROPERTIES	
Water absorption capacity	EN ISO 10545-03	< 0,5%
Flexion resistance	EN ISO 10545-04	=> 45 N/mm ²
Abrasion resistance (glazed Ceramic)	EN ISO10545-07	III
Thermal shock resistance	EN ISO 10545-09	It stands the test
Cracking resistance	EN ISO 10545-11	It stands the test
Frost resistance	EN ISO 10545-12	It stands the test

CHEMICAL PROPERTIES		
Resistance to acids	EN ISO 10545-13	GHA
Resistance to alcalis	EN ISO 10545-13	GHA
Resistance to cleaning products	EN ISO 10545-13	GLA
Resistance to chemical products in swimming pool water	EN ISO 10545-13	GLA
Stains resistance	EN ISO 10545-14	3

ANTI-SLIP CHARACTERISTICS









ROD. DORIAN GRAPHITE 7,5X60

REFERENCE SIZE (cm) THICKNESS (mm) GROUP

A019269 7,5x60 9,20 PC BIA GL

DIMENSIONS AND SURFACE PROPERTIES

PHYSICAL PROPERTIES

Frost resistance EN ISO 10545-12 It stands the test









DORIAN BROWN RECT 60X120

REFERENCE SIZE (cm) THICKNESS (mm) GROUP

A033147 60x120 10,20 PC BIA GL



DIMENSIONS AND SURFACE PROPERTIES

Size, thickness, side straightness, flatness, orthogonality UNE-EN 14411 It accomplished all requeriments

PHYSICAL PROPERTIES		
Water absorption capacity	EN ISO 10545-03	< 0,5%
Flexion resistance	EN ISO 10545-04	$=>45 \text{ N/mm}^2$
Abrasion resistance (glazed Ceramic)	EN ISO10545-07	III
Thermal shock resistance	EN ISO 10545-09	It stands the test
Cracking resistance	EN ISO 10545-11	It stands the test
Frost resistance	EN ISO 10545-12	It stands the test

CHEMICAL PROPERTIES			
Resistance to acids	EN ISO 10545-13	GHA	
Resistance to alcalis	EN ISO 10545-13	GHA	
Resistance to cleaning products	EN ISO 10545-13	GLA	
Resistance to chemical products in swimming pool water	EN ISO 10545-13	GLA	
Stains resistance	EN ISO 10545-14	3	

ANTI-SLIP CHARACTERISTICS









DORIAN BROWN RECT 60X60

REFERENCE SIZE (cm) THICKNESS (mm) GROUP

A018637 60X60 9,10 PC BIA GL



DIMENSIONS AND SURFACE PROPERTIES

Size, thickness, side straightness, flatness, orthogonality UNE-EN 14411 It accomplished all requeriments

PHYSICAL PROPERTIES		
Water absorption capacity	EN ISO 10545-03	< 0,5%
Flexion resistance	EN ISO 10545-04	=> 45 N/mm ²
Abrasion resistance (glazed Ceramic)	EN ISO10545-07	III
Thermal shock resistance	EN ISO 10545-09	It stands the test
Cracking resistance	EN ISO 10545-11	It stands the test
Frost resistance	EN ISO 10545-12	It stands the test

CHEMICAL PROPERTIES			
Resistance to acids	EN ISO 10545-13	GHA	
Resistance to alcalis	EN ISO 10545-13	GHA	
Resistance to cleaning products	EN ISO 10545-13	GLA	
Resistance to chemical products in swimming pool water	EN ISO 10545-13	GLA	
Stains resistance	EN ISO 10545-14	3	

ANTI-SLIP CHARACTERISTICS









DORIAN BROWN RECT 30X60

REFERENCE SIZE (cm) THICKNESS (mm) GROUP

A018641 30X60 9,40 PC BIA GL



DIMENSIONS AND SURFACE PROPERTIES

Size, thickness, side straightness, flatness, orthogonality UNE-EN 14411 It accomplished all requeriments

PHYSICAL PROPERTIES		
Water absorption capacity	EN ISO 10545-03	< 0,5%
Flexion resistance	EN ISO 10545-04	$=>45 \text{ N/mm}^2$
Abrasion resistance (glazed Ceramic)	EN ISO10545-07	III
Thermal shock resistance	EN ISO 10545-09	It stands the test
Cracking resistance	EN ISO 10545-11	It stands the test
Frost resistance	EN ISO 10545-12	It stands the test

CHEMICAL PROPERTIES			
Resistance to acids	EN ISO 10545-13	GHA	
Resistance to alcalis	EN ISO 10545-13	GHA	
Resistance to cleaning products	EN ISO 10545-13	GLA	
Resistance to chemical products in swimming pool water	EN ISO 10545-13	GLA	
Stains resistance	EN ISO 10545-14	3	

ANTI-SLIP CHARACTERISTICS









ROD. DORIAN BROWN 7,5X60

REFERENCE SIZE (cm) THICKNESS (mm) GROUP

A019271 7,5x60 9,50 PC BIA GL

DIMENSIONS AND SURFACE PROPERTIES

PHYSICAL PROPERTIES

Frost resistance EN ISO 10545-12 It stands the test










LAVABO NISO IZQ.

REFERENCE SIZE (cm) THICKNESS (mm) GROUP

A040865 0,00 PC BIA GL



DIMENSIONS AND SURFACE PROPERTIES

PHYSICAL PROPERTIES

Frost resistance EN ISO 10545-12 It stands the test










LAVABO NISO DCHA.

REFERENCE SIZE (cm) THICKNESS (mm) GROUP

A040866 0,00 PC BIA GL



DIMENSIONS AND SURFACE PROPERTIES

PHYSICAL PROPERTIES

Frost resistance EN ISO 10545-12 It stands the test










LAVABO DE PIE ROMA

REFERENCE SIZE (cm) THICKNESS (mm) GROUP

A040867 0,00 PC BIA GL



DIMENSIONS AND SURFACE PROPERTIES

PHYSICAL PROPERTIES

Frost resistance EN ISO 10545-12 It stands the test










LAVABO AXEL IZQ.

REFERENCE SIZE (cm) THICKNESS (mm) GROUP

A040868 0,00 PC BIA GL



DIMENSIONS AND SURFACE PROPERTIES

PHYSICAL PROPERTIES

Frost resistance EN ISO 10545-12 It stands the test










LAVABO AXEL DCHA.

REFERENCE SIZE (cm) THICKNESS (mm) GROUP

A040869 0,00 PC BIA GL



DIMENSIONS AND SURFACE PROPERTIES

PHYSICAL PROPERTIES

Frost resistance EN ISO 10545-12 It stands the test










LAVABO AXEL CEN.

REFERENCE SIZE (cm) THICKNESS (mm) GROUP

A040870 0,00 PC BIA GL



DIMENSIONS AND SURFACE PROPERTIES

PHYSICAL PROPERTIES

Frost resistance EN ISO 10545-12 It stands the test










LAVABO AXEL DOBLE 160

REFERENCE SIZE (cm) THICKNESS (mm) GROUP

A040871 0,00 PC BIA GL



DIMENSIONS AND SURFACE PROPERTIES

PHYSICAL PROPERTIES

Frost resistance EN ISO 10545-12 It stands the test










LAVABO ENEA IZQ.

REFERENCE SIZE (cm) THICKNESS (mm) GROUP

A040872 0,00 PC BIA GL



DIMENSIONS AND SURFACE PROPERTIES

PHYSICAL PROPERTIES

Frost resistance EN ISO 10545-12 It stands the test










LAVABO ENEA DCHA.

REFERENCE SIZE (cm) THICKNESS (mm) GROUP

A040873 0,00 PC BIA GL



DIMENSIONS AND SURFACE PROPERTIES

PHYSICAL PROPERTIES

Frost resistance EN ISO 10545-12 It stands the test










LAVABO ENEA CEN.

REFERENCE SIZE (cm) THICKNESS (mm) GROUP

A040874 0,00 PC BIA GL



DIMENSIONS AND SURFACE PROPERTIES

PHYSICAL PROPERTIES

Frost resistance EN ISO 10545-12 It stands the test










LAVABO ENEA DOBLE 160

REFERENCE SIZE (cm) THICKNESS (mm) GROUP

A040875 0,00 PC BIA GL



DIMENSIONS AND SURFACE PROPERTIES

PHYSICAL PROPERTIES

Frost resistance EN ISO 10545-12 It stands the test





